(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau

AIPO PMPI



(43) International Publication Date 31 December 2003 (31.12.2003)

PCT

(10) International Publication Number WO 2004/001270 A1

(51) International Patent Classification⁷: 33/01

F16L 33/24,

(21) International Application Number:

PCT/GB2003/002629

(22) International Filing Date: 19 June 2003 (19.06.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0214449.1 0217263.3 22 June 2002 (22.06.2002) GB 25 July 2002 (25.07.2002) GB

- (71) Applicant (for all designated States except US): OYS-TERTEC PLC [GB/GB]; Southgate, Market Weighton, York, North Yorkshire YO43 3BG (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): GLAZE, Alan [GB/GB]; IBP Limited, Whitehall Road, Tipton, West Midlands DY4 7JU (GB).

- (74) Agent: GODDARD, David, John; Harrison Goddard Foote, Orlando House, 11c Compstall Road, Marple Bridge, Stockport SK6 5HH (GB).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


of inventorship (Rule 4.17(iv)) for US only

Published:

with international search report

[Continued on next page]

(54) Title: COUPLING OF TUBULAR MEMBERS



(57) Abstract: A device (20) or restricting removal from the end of a tubular member (2) of a collar (4) or the like located on the tubular member (2) and a method using the device (20), the device (20) comprising an axially extending portion (22) for engagement in the end of the tubular member (2) and a radially outwardly extending portion (28) which in use is located outside the end of the tubular member (2) and which extends radially outwardly to a greater diameter than the internal diameter of the collar (4), thereby to restrict removal of the collar (4) from the end of the tubular member (2). In addition there is provided (20) for sealing the axially facing end of a tubular member (2), the device (20) comprising an axially extending portion (22) for engagement in the tubular member (2), a radially outwardly extending portion (28) which in use is located outside the tubular member (2) and a sealing means (48) for sealing between the radially outwardly extending portion (28) and the axially facing end (54) of the tubular member (2).